



**HOOD ASSEMBLY CONSISTS OF:**

- 1 x HOOD + COVER: PBT UL 94 V-0; BLACK
- 1 x PRESS INSERT: PBT UL 94 V-0; BLACK
- 2 x JACKSCREWS: BRASS; NICKEL PLATED
- 2 x SCREW FOR STRAIN RELIEF: STEEL; ZINC PLATED
- 1 x COVER SCREWS: STEEL; NICKEL PLATED
- 1 x STRAIN RELIEF: STEEL; NICKEL PLATED

Pos.	$\phi F$ cable diameter	
	WITH PRESS INSERT	WITHOUT PRESS INSERT
9	4.0 - 6.3	6.4 - 8.6
15	4.0 - 6.3	6.4 - 8.6
25	6.5 - 8.5	8.6 - 12.0
37	8.5 - 10.9	11.0 - 14.0
50	8.5 - 10.9	11.0 - 14.0

**TECHNICAL DATA:**

- TEMPERATURE RANGE: -40°C to +125°C (b)

Directive 2002/95/EC RoHS compliant

Pos.	A	B	C	D	E	Part No.	
						Bulk package	Single package
9	32.9	25.0	39.5	41.9	16.4	165X14559X	165X14559XE
15	41.2	33.3	45.5	47.9	16.4	165X14569X	165X14569XE
25	54.9	47.0	52.5	54.9	16.4	165X14579X	165X14579XE
37	71.4	63.5	55.0	57.9	18.8	165X14589X	165X14589XE
50	69.0	61.1	55.0	57.9	19.6	165X14599X	165X14599XE

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.  
 OWNERSHIP AND COPYRIGHT OF CONEC GmbH  
 DO NOT ALTER CAD DRAWING BY HAND

tolerance				scale: 1:1	
2010		date	name		material: SEE TECHNICAL DATA
drawn	17.12.	Henneboel		title: <b>PLASTIC HOOD</b> WITH SIDE CABLE EXIT 9 to 50pos.	
appd.	17.12.	Fischer			
norm					
d-old					
3 x b	Ä5350	17.09.2014	E.Mick.	dwg no:	AutoCAD
a	Origin			16K1A2754	
rev.	description	date	name	product no:	SEE TABLE

