



0
0
0
0
0
0
0
0

[Request a quote](#)

[Catalog](#)

0B
No contacts / Accessory
61
0.00 - 0.00 mm

TECHNICAL DETAILS

Mechanics

| | |
|-------------------|---|
| Shell Style/Model | BRD*: Cap for free receptacle |
| Keying | No keying |
| Housing Material | POM (Polyoxymethylene) shell without treatment, silicone gasket |
| Cable Fixing | ∅ 0 - 0 mm |
| Variant | |

Performance

| |
|---------------|
| Configuration |
| Insulator |
| Rated Current |


Others

| |
|---|
| Endurance (Shell): 5000 |
| Temp (min / max): -55° C / +250° C |
| Humidity (max): <=95% [at 60 deg C / 140 F] |
| Vibration: 15 g [10 Hz - 2000 Hz] |
| Shock Resistance: 100 g [6 ms] |

Salt Spray Corrosion: >1000 hr
Climatical Category: 50/175/21
Shielding (min): 75 dB (10 MHz)
Shielding (min): 40 dB (1 GHz)
IP Rating: 61

DRAWINGS

Draws



Dimensions

| | A | B | L | M | N |
|-----|------|------|------|------|------|
| mm. | 10 | 12.5 | 11 | 4.8 | 85 |
| in. | 0.39 | 0.49 | 0.43 | 0.19 | 3.35 |

RECOMMENDED BY LEMO

Tools

None

Cables