


Material:



- Conductor: 26AWG $7 \times 0.16 \pm 0.015$ mm
- Conductor Insulation color coding: (1) White/Orange, (1) Orange, (1) White/Green, (1) Green, (1) Blue, (1) White/Blue, (1) White/Brown, (1) Brown
- Cable jacket printing: CM (UL) C(UL) 4P 26AWG UTP CAT.5E PATCH CABLE ISO/IEC 11801 & EN 50288 & ANSI/TIA-568-C.2
- Wiring T568B Color
- P1 & P2 Contact plug: RJ45 8P8C 3μ pc UL 94V-2
- Cable tie: White
- Cable jacket color: Black, White, Blue, or Grey
- Dielectric strength: 2.5KV dc-2seconds
- Working temperatures: $-20^{\circ}\text{C} \sim +60^{\circ}\text{C}$

PIN OUT

P1	WIRE COLOR	P2
1	ORANGE/WHITE	1
2	ORANGE	2
3	GREEN/WHITE	3
6	GREEN	6
4	BLUE	4
5	BLUE/WHITE	5
7	BROWN/WHITE	7
8	BROWN	8



Unit: mm



Order Code: DK-1511-26-xxx/x
 Order lengths in feet: 1,3,5,7,10,15, 20,25,50,100
 Cable Jacket colors: Black(BL), White(WH), Blue(B), or Grey(G)

Scale	Free					Date	Name
TOLERANCE							
X.	± 0.3					Drawn	23.04.13
X.X	$\pm X$					Approved	23.04.13
X.XX	$\pm X$						
DIM	TOL						
X.°	$\pm X^{\circ}$						
X.X°	$\pm X^{\circ}$	ⓐ	Drawn	23.04.13	Wilson		
Angle	TOL	Id.	Modification	Date	Name		



Title	
Cat5e UTP Patch cable Unshielded/Booted, 26AWG, gold plating	
ASSMANN WSW-No. DK-1511-26-xxx/x	
Drawing-No.	rev00
Replace	Sheet 1/1