



PC card drilling dimensions(after plating)
(thickness 1.60±0.20mm)

GENERAL CHARACTERISTICS AND ROHS INFORMATIONS:
SEE DRAWING C01-8646-0000

SHELL	A±0.38	B±0.12	C±0.10	D±0.25	E±0.07	TIN LEAD	LEAD FREE
09	30.81	24.99	16.96	16.21	10.96	D09S24A.GL00	D09S24A.GL00LF
15	39.14	33.32	25.18	24.54	19.18	D15S24A.GL00	D15S24A.GL00LF
25	53.03	47.04	39.12	38.25	33.12	D25S24A.GL00	D25S24A.GL00LF
37	69.32	63.50	55.68	54.71	49.68	D37S24A.GL00	D37S24A.GL00LF

Plating: 4 --> flash AU
Plating: 6 --> 0.76µ AU

rev	ecn no	dr	date
B	-	CJA	1999/10/18
C	LS05-001	MPE	2005/01/11
D	LS05-0056	MPE	2005/06/28
E	LS06-0097	LGO	2006/07/28
F	LS08-0172	MPE	2008/08/13
G	I10-0059	NG	2010-02-23

www.fciconnect.com		surface		tolerance std		projection	
ISO 1302		ISO 406 ISO 1101		ANGULAR		A3	
TOLERANCES UNLESS OTHERWISE SPECIFIED		SPECIFIED		LINEAR		Scale	
0.X		±0.1		0.XX		2	
0.XXX		±0.1		0.XXX		110-0059	
Product family		D-SUB		Spec ref		-	
Dr JOURBERT		1999/10/18		Chr PESSION		1999/10/18	
Eng NIRMAL GEORGE		2010-02-23		Chr NIRMAL GEORGE		2010-02-23	
Appr SUDHIR VARMA		2010-02-23		Appr SUDHIR VARMA		2010-02-23	
FCI logo		FEMALE CONNECTOR EUROPE		FCI logo		CUSTOMER	
STRAIGHT STB FOR PCB 1.60mm		C01-8646-0494		sheet 1 of 1		Rev. G	

European Views

mm